



## Barbed Clips - PRC Series

An economical fastener which caters for a wide range of panel thickness and materials

Part Number	Hole Size	Panel Thickness	Head Diameter B	Head Style	Head Height A	Length C
04-PRC513*	4.8	0.6-9.3	9.5	A	1.8	12.7
04-PRC515	4.8	0.8-8.4	11.2	B	1.7	14.3
04-PRC517	4.8	3.2-9.3	11.1	D	1.8	16.3
04-PRC517K	4.8	2.5-15.2	11.7	A	1.0	17.5
04-PRC518P**	4.8	3.2-11.4	7.2	C	1.7	17.8
04-PRC610	6.4	5.1-5.5	18.3	A	2.3	10.8
04-PRC611	6.4	2.7-7.6	17.8	A	2.5	11.1
04-PRC619	6.4	3.8-13.6	12.6	A	1.9	19.9
04-PRC620	6.4	3.8-13.6	17.8	A	2.5	20.3
04-PRC725	7.1	4.3-19.6	17.6	A	2.3	24.8
04-PRC723	7.1	2.4-12.7	15.9	A	2.8	22.6
04-PRC1028BM*	10.0	1.5-20.0	21.8	-	3.5	28.2

**Material: Black Nylon 6/6 – UV Resistant except for PRC518P which is black polypropylene**  
 \*Available in white \*\*Available in Natural

Headstyles:




## Special Barbed Clips - XTS Series

Variety of hole sizes and panel thicknesses • Clips can be used in blind hole applications.

Part Number	Hole Size	Panel Thickness	Head Diameter B	Head Height A	Length C
04-XTS308	3 - 3.3	3.4-6.3	6.4	2.0	7.8
04-XTS511	4.6 - 4.8	0.9-5.3	11.1	1.9	11.1
04-XTS610	6.1 - 6.6	1.9-4.7	15.5	3.0	9.8
04-XTS614*	6.35 - 6.48	1.8-10.16	17.8	2.54	13.8
04-XTS620	6.35	3.2-17.4	12.7	1.7	19.9
04-XTS632	6.32	1.3-22.2	19.0	2.8	31.8
04-XTS749	7.14	20.6-40.1	15.1	1.3	49.1
04-XTS817	8.1	3.0-12.7	12.7	1.3	16.6

04-XTS308    04-XTS511    04-XTS610    04-XTS614    04-XTS620    04-XTS632    04-XTS749    04-XTS817



**Material: Black Nylon 6/6 – UV Resistant**  
 \*Available in Natural

